

edito KSM347



Introducing a new industrial Kiosk Printer family with different options. The range includes a base model, a model with output control (push and pull detection) -O, a presenter model -P and a presenter and retractor model -R with internal print possibility. The sophisticated firmware allows the user to control the actions of the printer and to set-up the printer easily. Many internal fonts are already implemented. Additional fonts can be downloaded for character-sizes from 6x8 to 64x64 dots. The printer can operate with paper width from 58 mm to 83 mm. An illuminated bezel indicates an available ticket very clearly.



Technical specifications:

Models	edito KSM347 series
Method	Thermal line dot printing (Seiko CAPM347C mechanism)
Number of dots/line	640
Resolution	8 dots/mm (200dpi)
Paper width	58 mm to 83 mm
Printing width	52mm (416 dots) to 80mm (640 dots)
Print speed max.	200 mm/s.
Paper loading method	Auto-Load
Paper roll diameter **	200mm max. (inner core 25mm min.)
Tension unit	Integrated in flex paper channel
Character matrix standard (dots)	8x16 / 12x24
Character Matrix for user code pages	6x8 to 64x64 (x-y) dots, free definition
Internal code pages	CP -437,-850,-852,-858,-860,-863,-865,-1250,-1251,-1252
User code pages	20 user defined code pages max. (proportional characters possible)
Flash graphic storage	20 max
Internal Flash memory	512 kByte
Input buffer	8 kByte
Interfaces:	USB and serial interface / additional LAN as option
RS232	fix 115.200 bps, 8 data bits, no parity, 1 stop bit (Xon/Xoff) (RTS-CTS)
USB	2.0
Ethernet	100 MB (DHCP)
Emulaton	ESC POS / (Windows Driver)
Sensors (more sensors integrated for internal functionality)	2 x paper end, paper near-end, black mark, head open, ticket removed
Power supply	24 V DC
Cutter type	slide type
Cutter methode	full & partial cut (partial cut only for base model)
Service live pulse activation (pulse) *	200.000.000
Service live abrasion resistance (m) *	200.000 (printer mechanism) with specified paper
Service life cutter (cuts) *	Base model 1.500.000 (other models 1.000.000 with specified paper)
Operating temperature (°C)	-20 °C to 70°C (Non condensing)
Storage temperature (°C)	-25 °C to 75°C (Non condensing)
Mass (g)	Base model 1290g / -O 1510g / -P 1560g / -R 1645g
Dimensions (W x D x H) ***	Base model (128 x 127 x 103,5) -O/ -P/ -R (128 x 192 x 103,5)

* For specified papers, ** can be lower by some roll positions, ***without paper holder arm, without connectors, including bezel

Models (functions):

Model* / Interface	Base model	Output Control	Presenter	Retract	Internal print	Serial and USB	Serial USB and LAN
edito KSM347-S/U	X					X	
edito KSM347-S/U/E	X						X
edito KSM347O-S/U		X				X	
edito KSM347O-S/U/E		X					X
edito KSM347P-S/U			X			X	
edito KSM347P-S/U/E			X				X
edito KSM347R-S/U			X	X	X	X	
edito KSM347R-S/U/E			X	X	X		X

* All models have flex-paper channel and paper arm included.



All Interfaces connectors on backside of the printer, also 2 buttons and the power connector. 4 status-LEDs located at the backside. Additionally a status can be indicated on the illuminated bezel. The illumination of the bezel can be controlled by software or by automatic mode.

